Texas Commission on Environmental Quality BACKFLOW PREVENTION ASSEMBLY TEST AND MAINTENANCE REPORT

The following form must be completed for each assembly tested. A signed and dated original must be submitted to the public water supplier for recordkeeping *purposes. NAME OF PWS: Dripping Springs WSC PWS ID#: 1050013 **PWS MAILING ADDRESS:** 101 Hays St. Ste. 406 Dripping Springs Tx 78620 Coralin Taylor **PWS CONTACT PERSON:** ADDRESS OF SERVICE: The backflow prevention assembly detailed below has been tested and maintained as required by commission regulations and is certified to be operating within acceptable parameters. TYPE OF BACKFLOW PREVENTION ASSEMBLY (BPA): Reduced Pressure Principle (RPBA) Reduced Pressure Principle-Detector (RPBA-D) Double Check Valve (DCVA) Double Check-Detector (DCVA-D) Pressure Vacuum Breaker (PVB) Spill-Resistant Pressure Vacuum Breaker (SVB) Manufacturer: Size: Model Number: **BPA Location:** Serial Number: **BPA Scrvcs:** Reason for test: New Replacement Old Model/Serial # Existing \square Is the assembly installed in accordance with manufacturer recommendations and/or local codes? \square No ☐ Yes | Is the assembly installed on a non-potable water supply (auxiliary)? ☐ Yes ☐ No **TEST RESULT** Reduced Pressure Principle Assembly (RPBA) PVB & SVB PASS **DCVA** Relief Valve Check Valve Air Inlet 2nd Check*** FAIL 1st Check psid Held at Held at **Initial Test** psid Opened at psid Opened at Held at psid Date: Did not open psid Closed Tight Closed Tight Leaked Time: Did not open \square Leaked Leaked Did it fully open (Yes □ /No □) Repairs and Materials Used** Test After Repair Held at psid Held at psid Opened at psid Opened at Held at psid Date: Closed Tight Closed Tight psid Time: *** 2nd check: numeric reading required for DCVA only Differential pressure gauge used: Potable: Non-Potable: Make/Model: SN: Date tested for accuracy: Remarks: Company Name: Licensed Tester Name (Print/Type): Company Address: Licensed Tester Name (Signature): Company Phone #: **BPAT License #** License Expiration Date:

The above is certified to be true at the time of testing.

** USE ONLY MANUFACTURER'S REPLACEMENT PARTS

^{*} TEST RECORDS MUST BE KEPT FOR AT LEAST THREE YEARS [30 TAC §290,46(B)]